



5 LABEL		1PC	W=30.0MM, L=110.0MM, CONTENT: SEE "A"	
4 IDC D-SUB		1PC	IDC D-SUB 37 FEMALE W/SR, COLOR: BLACK WITH #4-40 HEX SCREWLOCK	
3 CONTACT		26PCS	MATERIAL: BRONZE, NICKEL UNDERCOATED JMT P/N: A2005TOB-00 OR EQ	
2 26P HOUSING		1PC	MATERIAL: PPO, UL94V-1, COLOR: BLACK PITCH: 2.0MM, 2X13 JMT P/N: A200SH02-2*13P OR EQ	E144544
1 FLAT CABLE		1PC	UL2651 #28x26C, PITCH: 1.27MM, JACKET: PVC, COLOR: GRAY	E209329
No.	ITEM	Q'TY	DESCRIPTION	UL NO.

NOTES:

- ALL DIMENSIONS ARE "MM".
- ANY OPEN, MISWIRING, SHORT & INTERMITTENT ARE NOT PERMITTED.
- CONNECTION RESISTANCE: 2.0Ω
- INSULATION RESISTANCE: 20MΩ/300V DC MIN
- THE PRODUCT MUST BE COMPLY WITH THE DIRECTIVE OF ROHS.
- PACKAGE: 1PC/BAG.

WIRE CONNECTION TABLE	
J1	WIRE COLOR
1	RED
2	GRAY
3	GRAY
4	GRAY
5	GRAY
6	GRAY
7	GRAY
8	GRAY
9	GRAY
10	GRAY
11	GRAY
12	GRAY
13	GRAY
WIRE CONNECTION TABLE	
J1	WIRE COLOR
1	GRAY
2	GRAY
3	GRAY
4	GRAY
5	GRAY
6	GRAY
7	GRAY
8	GRAY
9	GRAY
10	GRAY
11	GRAY
12	GRAY
13	GRAY
14	GRAY
15	GRAY
16	GRAY
17	GRAY
18	GRAY
19	GRAY
20	GRAY
21	GRAY
22	GRAY
23	GRAY
24	GRAY
25	GRAY
26	GRAY
J1	WIRE COLOR
J2	WIRE COLOR

PART NO. (INTENDED USE)		TITLE: CABLE HARNESS, 2x13, 2MM CONNECTOR TO IDC D-SUB FEMALE	
6980516 REV A		6980516 REV A	
APPD: WUFUHU 06/13/16		DWG NO: GL-WH0516	
CHKD: WUZUJIAN 06/13/16		SCALE: SHEET REV.	
DR: JASON 06/13/16		NONE 1/1 A	