



12	GRAY	12
11	GRAY	11
10	GRAY	10
9	GRAY	9
8	GRAY	8
7	GRAY	7
6	GRAY	6
5	GRAY	5
4	GRAY	4
3	GRAY	3
2	GRAY	2
1	RED	1
J1	WIRE COLOR	J2
WIRE CONNECTION TABLE		

5	LABEL	1PC	W=30.0MM, L=80.0MM, CONTENT: SEE "A"
4	12P IDC	1PC	MATERIAL: PBT, UL94V-0, PITCH: 2.0MM, IDC SOCKET 2X6 W/NOSE, W/SR, COLOR: BLACK
3	CONTACT	12PCS	MATERIAL: PHOSPHOR BRONZE, TIN PLATED WIRE RANGE: #30~#26, JST P/N: SSHL-002T-P0.2 JCTC P/N: 11257TOP-2E
2	12P HOUSING	1PC	MATERIAL: PBT, UL94V-0, COLOR: NATURAL WHITE PITCH: 1.25MM, 1X12 JST P/N: CHR-12V-S JCTC P/N: 11257H00-12P-L
1	FLAT CABLE	1PC	UL2651 #28X12C, PITCH: 1.0MM, JACKET: PVC, COLOR: GRAY
No.	ITEM	Q'TY	DESCRIPTION
			UL NO.

- NOTES:
- ALL DIMENSIONS ARE "MM".
 - ANY OPEN, MISWIRING, SHORT & INTERMITTENT ARE NOT PERMITTED.
 - CONNECTION RESISTANCE: 2.0Ω
INSULATION RESISTANCE: 20MΩ
HI-POT VOLTAGE: 300V DC
HI-POT DURATION: 10mS
 - THE PRODUCT MUST BE COMPLY WITH THE DIRECTIVE OF ROHS.
 - PACKAGE: 1PC/BAG.

X.:±	.XX:±	X':±	.XX':±	PART NO.(INTENDED USE)	TITLE: CABLE HARNESS, 1X12, 1.25MM CONNECTOR TO 2X6PIN 2MM FEMALE IDC SOCKET
.X:±0.5	.XXX:±	.X':±	.XXX':±	6980514 REV A	
				APPD: WUFUHU 04/21'15	DWG NO.: GL-GH750
				CHKD: WUZUJIAN 04/21'15	SCALE SHEET REV.
				DR: JASON 04/21'15	NONE 1/1 A



G-LINKS CO.