



WIRING CHART

A	COLOR	B
1	RED	1
2	GREY	2
3	GREY	3
4	GREY	4
5	GREY	5
6	GREY	6
7	GREY	7
8	GREY	8
9	GREY	9
10	GREY	10
11	GREY	11
12	GREY	12
13	GREY	13
14	GREY	14
15	GREY	15
16	GREY	16
17	GREY	17
18	GREY	18
19	GREY	19
20	GREY	20
21	GREY	21
22	GREY	22
23	GREY	23
24	GREY	24
25	GREY	25
26	GREY	26
27	GREY	27
28	GREY	28
29	GREY	29
30	GREY	30

NO.	ITEM.	Q'TY	DESCRIPTION	UL / CSA No.
1	WIRE	1pcs	UL/CSA UL2651#28 30P GRAY PH: 1.0mm	
2	HOUSING	1pcs	L-5mm 2x15 DIAL ROWS JST ZPDR-30V-S (94-V0)	
3	TERMINAL	30pcs	JST SZPD-002T-P0.3	
4	CONN	1pcs	IDC 2.0mm 2x15 30P NOSE/SR SOCKET BLACK OR ASSMANN-AWP2-30-7241-T-R OR EQ	
5	LABEL	1pcs	TRANSPARENT POLYESTER SEE DETAIL "A"	

X:±		.XX:±	X':±	.XX':±	PART NO.(INTENDED USE)	
X:±0.5		.XXX:±	.X':±	.XXX':±	6981504 REV A	
					TITLE: CABLE HARNESS, DAQ I/O 1.5mm Connector to 2x15pin 2mm Female IDC Socket	
					DWG NO.: GL-GH583	
					APPD: WUFUHU 02/07'13	
					CHKD: WUZUJIAN 02/07'13	
					DR: MERVYN 02/07'13	
					SCALE SHEET REV.	
					NONE 1/1 A	

DETAIL "A"

**RoHS**  
compliant

NOTES:

1. ALL DIMENSIONS ARE "MM".
2. THE PRODUCT MUST BE COMPLY WITH THE DIRECTIVE OF ROHS.
3. PACKAGE: 1PC/BAG.

