



REV. A	ECO. NO.	NO.	APPD
			WU
			07/28'16

J1	WIRE COLOR	J2	WIRE COLOR
1	RED	1	RED
2	GREY	20	GREY
3	GREY	2	GREY
4	GREY	21	GREY
5	GREY	3	GREY
6	GREY	22	GREY
7	GREY	4	GREY
8	GREY	23	GREY
9	GREY	5	GREY
10	GREY	24	GREY
11	GREY	6	GREY
12	GREY	25	GREY
13	GREY	7	GREY
14	GREY	26	GREY
15	GREY	27	GREY
		28	GREY
		29	GREY
		30	GREY
		31	GREY
		32	GREY
		33	GREY
		34	GREY

No.	ITEM	Q.TY	DESCRIPTION
5	LABEL	1PC	W=30.0MM, L=110.0MM, CONTENT:SEE "A"
4	D-SUB+ SCREWS	1SETS	IDC D-SUB 37 FEMALE W/SR, COLOR:BLACK WITH 4#40 HEX SCREWLOCK 4.75x11.8MM
3	CONTACT	30PCS	MATERIAL: COPPER ALLOY TIN PLATED WIRE RANGE: #28~#24, JST P/N: SZPD-002T-P0.3
2	30P HOUSING	1PC	MATERIAL:PBT, UL94V-0, COLOR:NATURAL WHITE PITCH:1.5MM, 2X15 JST P/N: ZPDR-30V-S E60389
1	FLAT CABLE	1PC	UL2651 #28x30C, PITCH:1.27MM, JACKET:PVC, COLOR:GRAY E209329

DETAIL "A"

- NOTES:
- ALL DIMENSIONS ARE "MM".
  - ANY OPEN, MISWIRING, SHORT & INTERMITTENT ARE NOT PERMITTED.
  - Connection Resistance : 2.0Ω  
Insulation Resistance : 20MΩ  
Hi-POT Voltage : 300V DC  
Hi-POT Duration : 10mS
  - THE PRODUCT MUST BE COMPLY WITH THE DIRECTIVE OF ROHS.
  - PACKAGE: 1PC/BAG.

PART NO.(INTENDED USE)		TITLE: CABLE HARNESS, DAQ I/O	
6980518 REV A		1.5mm Connector to 2x15pin 2mm Female IDC DB37F	
APPD: WUFUHU 07/28'16		DWG NO.: GL-GH790	
CHKD: WUZUJIAN 07/28'16		SCALE: SHEET REV.	
DR: JASON 07/28'16		NONE 1/1 A	



**G-LINKS CO.**