


NOTES:

1. ALL DIMENSIONS ARE "MM".
2. ANY OPEN, MISWIRING, SHORT & INTERMITTENT ARE NOT PERMITTED.
3. INSULATION RESISTANCE: 20M OHMS/300V DC MIN.
- ⚠ THE PRODUCT MUST BE COMPLY WITH THE DIRECTIVE OF RoHS.

SHELL	3/4 BRAID		1	1/4 BRAID & DRAIN WIRE		SHELL
	1/4 BRAID & DRAIN WIRE			3/4 BRAID		
4	BLACK		3			
3	GREEN	TWSIT PAIR	5			
2	WHITE	PAIR	7			
1	RED		9			
			4	BLACK		4
			6	GREEN	TWSIT PAIR	3
			8	WHITE	PAIR	2
			10	RED		1
J3	CABLE B		J1	CABLE A		J2

WIRE CONNECTION TABLE (C)



DETAIL "A"
SCALE 1:1



No.	ITEM	Q'TY	DESCRIPTION	PART NO.
9	H.S TUBE	1PC	I.D=#1.5MM UL224 COLOR: BLACK L=23.0MM	061-002-063
		2PCS	I.D=#1.5MM UL224 COLOR: BLACK L=10.0MM	
		1PC	I.D=#10.0MM UL224 COLOR: BLACK L=20.0MM	
(D)(B) 8	LABEL	1PC	L=40.0MM W=30.0MM CONTENT: SEE "A"	062-003-684
7	OUTER MOLDED	22gm	PVC, SHORE A: 85±3, UL94V-0 COLOR: BLACK(600-BLK-001)	071-001-005
6	INNER MOLDED	12gm	PE FOR MOLDED, COLOR: NATURAL	072-001-001
5	NUT	2PCS	BRASS, NICKEL PLATED, #4-40UNC, L=8.0MM	054-001-042
4	USB 4POS. FEMALE CONN. ("A" TYPE)	2PCS	CONTACT: BRASS, 30u" GOLD PLATED INSULATION COLOR: WHITE, UL94V-0 SHELL: NICKEL PLATED	022-002-743
3	CONTACT	9PCS	CONN TERM FEMALE 26-30AWG CRIM P/N: 77138-001LF	
2	10P HOUSING	1PC	CONN HOUSING 10POS 2MM W/KEY P/N: 10073599-010LF	
(C) 1	CABLE	2PCS	#28x1P+#24x2C+AL./MYLAR+DRAIN WIRE +BRAID+JACKET: PVC O.D=#4.4~4.5MM, UL2725 COLOR: 600-BLK-001	011-001-1520

Cable no. 6980602 Rev A
 USB2.0 Cable, Latching 2x5
 2mm to Dual Type A Socket
 Panel Mount



www.diamondsystems.com