



WIRING CHART

A	COLOR	B	RS232
3	BLACK	3	RXD
2	BLACK	2	TXD
1	RED	5	ISO_GND



DETAIL "A"



- NOTES:
1. ALL DIMENSIONS ARE "MM".
 2. THE PRODUCT MUST BE COMPLY WITH THE DIRECTIVE OF ROHS.
 3. PACKAGE: 1PC/ BAG.

REV.	ECO. NO.	NO.	APPD
A	REL.		YIER 12/23'10
B	CHANGE SPEC.		YIER 2/18'11
C	CHANGE SPEC.		YIER 4/27'11
D	CHANGE DB9F		YIER 6/8'11

NO.	ITEM.	Q'TY	DESCRIPTION	UL / CSA No.
1	WIRE	2PCS	UL/CSA 1007 #28 BLACK	E108485
2	WIRE	1PCS	UL/CSA 1007 #28 RED	E108485
3	CONN	1PCS	DB9F FEMALE SOCKET INSULATION BLACK	E144400
			TERMINAL G/F SHELL NI-PLATED	
4	SHELL	1SETS	SHELL R101-09B BLACK WITH SCREW	
5	HOUSING	1PCS	Molex 2.0mm 35507-0300	
6	TERMINAL	3PCS	Molex 50212-8100(Loose) / 50212-8000 (Reel)	
7	LABEL	1PCS	TRANSPARENT POLYESTER SEE DETAIL "A"	

X:±	.XX:±	X':±	.XX':±	TITLE:
.X:±0.5	.XXX:±	.X':±	.XXX':±	CABLE, SERIAL, 2mm to 1x DB9F
PART NO.(INTENDED USE)				DWG NO.:
6981050 REV B				GL-GH510
APPD: WJFUHU 6/8'11				SCALE SHEET REV.
CHKD: HOWARD 6/8'11				NONE 1/1
DR: XINGJU 6/8'11				D

